

**IN THE CLAIMS**

Pursuant to 37 CFR §1.121(c), the following listing, including the text of the claims in the amendment document will serve to replace all prior versions of the claims in the application, and incorporates the amendments made by this Paper.

Please amend claims 1 through 17, 20, 22 through 24, 26 and 29 as follows:

1           1. (Currently Amended) A method for processing and separating ~~an imbricate~~  
2 ~~formation of~~ flexible, flat objects during product feed, ~~comprising~~ comprised of:  
3                   continuously feeding ~~[[the items]]~~ flexible objects to a transfer module in  
4 an essentially regular imbricate formation ~~as to a transfer module and transferring the~~  
5 ~~[[items from]]~~ flexible objects fluently advance along a guide within said transfer module  
6 with leading lower edges of the flexible objects supported on a surface of the said transfer  
7 ~~module to a conveyor module, wherein flat objects are fluently fed to a guide within said~~  
8 ~~transfer module, and with a trailing edge of each flexible object lying over the leading~~  
9 lower edge of a subsequent flexible object;  
10               erecting the [[flat]] flexible objects during their conveyance are brought  
11 said product feed along the guide into an obliquely standing positions position by the  
12 guide with leading upper edges of the flexible objects exhibiting inclinations opposite to  
13 orientations of the flexible objects when initially erected [[,]]; and  
14               accommodating separation of the [[flat]] flexible objects from the obliquely  
15 standing positions with leading upper edges of the flexible objects exhibiting inclinations  
16 opposite to orientations of the flexible objects when erected, this position are separated in  
17 a defined number from the ~~remaining flat~~ flexible objects ~~by a separator remaining~~  
18 supported by the guide, and conveyed conveyance away from the transfer module by a

19 conveyor.

1           2. (Currently Amended) The method according to claim 1, ~~wherein~~ comprised of  
2 the ~~[[flat]]~~ flexible objects ~~are fed onto a surface of the guide and are conveyed lying in~~  
3 ~~an overlapping manner, wherein the trailing edge of a flat object lies over [[the]] a~~  
4 ~~leading edge of the subsequent flat object, and the objects during the transport said~~  
5 advance of the flexible objects over the surface of the guide surface the flexible objects  
6 are continuously ~~erected~~ rotated, ~~whereby on removal of the flat objects from the guide~~  
7 orientation of the flexible objects in said obliquely standing position ~~of the flat objects is~~  
8 inclined opposite to ~~a direction orientation of said conveyance~~ the flexible objects when  
9 erected.

1           3. (Currently Amended) The method according to claim 1, wherein the ~~[[flat]]~~  
2 flexible objects are folded sheets, ~~wherein the~~ whereby a fold of each folded sheet lies in  
3 a trailing manner ~~[[lies]]~~ over a respective subsequent folded sheet and the folded sheets  
4 ~~which stand obliquely on removal~~ standing at said conveyance away from the guide  
5 ~~means stand on [[their]] cut-edge side~~ sides.

1           4. (Currently Amended) The method according to claim 2, wherein the ~~[[flat]]~~  
2 flexible objects are folded sheets, wherein the fold of each folded sheet in a trailing  
3 manner lies over the respective subsequent folded sheet and the folded sheets which stand  
4 obliquely on removal from the guide ~~means stand on their~~ corresponding cut-edge ~~side~~  
5 sides of the folded sheets.

1           5. (Currently Amended) The method according to claim 1, wherein the ~~erection~~  
2 rotation of the ~~[[flat]]~~ flexible objects is effected by active braking or acceleration of the  
3 ~~[[flat]] flexible objects along~~ at least one edge by ~~way of~~ independently driving each of a  
4 plurality of conveyor means conveying elements disposed upon the guide.

1           6. (Currently Amended) The method according to claim 1, ~~wherein the flat~~  
2 ~~objects on removal are actively transferred into an obliquely standing position in the~~  
3 ~~conveying direction by way of folding-over means~~ comprised of contributing to said  
4 rotation by sequentially urging upper edges of the flexible objects in a direction of said  
5 advance.

1           7. (Currently Amended) The method according to claim 1, ~~wherein the flat~~  
2 ~~objects before removal are displaced transversely to their main conveying direction~~  
3 comprised of contributing to said rotation by individually regulating movement of a  
4 plurality of conveyors disposed along said guide to movingly engage the lower edges.

1           8. (Currently Amended) ~~A device for carrying out the~~ The method according to  
2 claim 1 ~~with a product feed, comprising a conveyor transfer module arranged after this~~  
3 ~~and with a conveyor module for removal of flat objects from the transfer module;~~

4 ~~wherein the transfer module contains a guide means which comprises a guide~~  
5 ~~surface which at least in regions is inclined with respect to the horizontal, and that on the~~  
6 ~~side proximal to the removal device there is arranged a brim or abutment,~~ comprised of  
7 contributing to said rotation by terminating said guide with an abutment oriented  
8 outwardly from said guide in a direction of said advance.

1           9. (Currently Amended) The ~~device according to~~ method of claim 8 1, wherein a  
2 surface of the guide surface at least in regions is designed concave or convex, or  
3 comprises at least two sections with a different ~~inclination of the guide surface~~  
4 inclinations.

1           10. (Currently Amended) The ~~device according to~~ method of claim 8 1, wherein  
2 ~~the inclination of~~ comprised of the guide surface at least in regions is having a downward  
3 inclination along a direction of said advance of more than 30°.

1           11. (Currently Amended) The ~~device according to~~ method of claim 8 1, wherein  
2 the guide ~~surface~~ comprises guide elements ~~which serve for the~~ providing regional  
3 acceleration and[[/or]] braking of the ~~flat~~ flexible objects.

1           12. (Currently Amended) The ~~device according to~~ method of claim 8 1, wherein  
2 ~~the brim or the~~ comprised of said transfer module having an abutment is ~~arranged~~  
3 ~~movable with respect~~ adjustably positionable relative to the guide means.

1           13. (Currently Amended) The ~~device according to~~ method of claim 8 1, wherein;  
2 ~~on that side of the guide means which is proximal to the removal device on that side of~~  
3 ~~the guide means which is proximal to the removal device, there are arranged active means~~  
4 ~~for separating~~ comprised of a separator disposed in proximity to said guide to make said  
5 separation of individual flexible objects or groups of the flexible objects.

1           14. (Currently Amended) The ~~device according to~~ method of claim 8 1, wherein  
2 ~~the brim or the abutment comprises~~ with the transfer module comprising a plurality of  
3 ~~movable elements conveying the~~ flexible objects in ~~the removal~~ a direction of said  
4 advance.

1           15. (Currently Amended) The ~~device according to~~ method of claim 8 1, wherein,  
2 ~~in the removal region of the objects, there are arranged means for~~ with the transfer  
3 module comprising a transverse shift disposed to transversely displacing displace the  
4 flexible objects obliquely standing within a terminal portion of said guide.

1           16. (Currently Amended) The ~~device according to~~ method of claim 8 1, wherein,  
2 comprised of a retainer disposed above the guide ~~means, there are arranged retaining~~  
3 ~~means acting on the~~ to act upon free ~~edge~~ edges of the objects.

1           17. (Withdrawn and Currently Amended) A guide, comprising:  
2           a path comprised of a first surface guiding leading lower edges of a  
3 plurality of flat, flexible items in an imbricate array to a curved surface extending  
4 downwardly from said first surface to an inclined surface, said path supporting the lower  
5 edges of the items during progressive transformation in orientation from leading to  
6 trailing lower edges of the items ~~into an imbricate array~~ while the items advance from  
7 said first surface and along said inclined surface; and  
8           an abutment extending transversely above said path to obstructively engage  
9 seriatim a lower portion of each of the items descending said ~~convexly curved~~ inclined  
10 surface and terminate said passage of each item along said inclined surface while the item

11 is obliquely erect with trailing lower edges.

1 18. (Withdrawn) The guide set forth in claim 17, comprised of a mechanism  
2 positioned to remove the items from engagement with said abutment by grasping the  
3 upper edges of a defined number of the items and sequentially lifting the items grasped  
4 away from said inclined surface.

1 19. (Withdrawn) The guide set forth in claim 17, comprised of said inclined  
2 surface exhibiting an inclination of more than thirty degrees from horizontal.

1 20. (Withdrawn and Currently Amended) A guide, comprising:  
2 an abutment; and  
3 a path comprised of a first surface positioned to continuously receive  
4 leading lower edges of a flow of flat, flexible items, and ~~a curved~~ an intermediate surface  
5 leading downwardly from said first surface to an inclined surface terminated by said  
6 abutment ~~while with~~ said path ~~supports~~ supporting the leading lower edges of the items  
7 ~~with while~~ said flow ~~of the flexible items advancing~~ advances the flexible items from said  
8 first surface ~~during and contributes to~~ progressive transformation in orientation of the  
9 items within the flow from upper edges of the items trailing into a formation with the  
10 items oriented obliquely erect at said abutment with the lower edges trailing.

1 21. (Withdrawn) The guide of claim 20, comprising a conveyor positioned to  
2 sequentially remove from said path, a defined number of the items embraced by said  
3 abutment.

1           22. (Withdrawn and Currently Amended)   The guide of claim 20, with said  
2 ~~curved~~ intermediate surface comprising a convex curve.

1           23. (Withdrawn and Currently Amended)   The guide of claim 20, with said  
2 ~~curved~~ intermediate surface comprising a concave curve.

1           24. (Withdrawn and Currently Amended)   The guide of claim 20, comprised of  
2 said first surface disposed to engage cut edges of the items ~~with~~ while folded edges of the  
3 items ~~trailing~~ trail the cut edges along said first surface.

1           25. (Withdrawn)   The guide of claim 20, comprised of said path engaging cut  
2 edges of the items with folded edges of the items trailing the cut edges along said first  
3 surface.

1           26. (Withdrawn and Currently Amended)   Guiding flexible, flat objects  
2 during product feed, comprised of:

3                   receiving leading lower edges of a flow of flat flexible items ~~upon~~ in an  
4 essentially regular imbricate formation onto a guide comprising a first surface leading to  
5 a curved surface extending downwardly from said first surface, with upper edges of the  
6 items trailing the lower edges during said flow along said first surface;

7                   aligning the items by precipitating a shift in orientation of the items within  
8 the flow as the items progress from said first surface via said curved surface and along a  
9 downwardly inclined surface ~~with~~ terminated by an abutment extending transversely

across said inclined surface causing an obstructive engagement of a lower portion of a forwardmost of the items while the forwardmost item is obliquely erect with lower edges of the items trailing the upper edges; and

removing a defined number of the items seriatim from said engagement.

27. (Withdrawn) Guiding, as set forth in clam 26, comprised of removing the items from said engagement by individually engaging the upper edges and sequentially lifting the items corresponding to the upper edges away from said inclined surface.

28. (Withdrawn) Guiding, as set forth in clam 26, comprised of providing said inclined surface with an inclination of more than thirty degrees from horizontal.

29. (Withdrawn and Currently Amended) Guiding flexible, flat objects during product feed, comprised of:

receiving cut leading edges of a flow of flat flexible items upon in an essentially regular imbricate formation onto a guide comprising a first surface leading to a curved surface extending downwardly from said first surface, with folded edges of the items trailing the cut edges during said flow along said first surface;

aligning the items within the flow by allowing the flow to progress from said first surface via said curved surface and along a downwardly inclined surface with terminated by an abutment extending transversely across said inclined surface causing an obstructive engagement of a lower portion of a forwardmost of the items while the forwardmost item is obliquely erect with folded edges of the items leading the cut edges; and



13 removing a defined number of the items seriatim from said engagement.

1 30. (Withdrawn) Guiding, as set forth in clam 29, comprised of removing the  
2 items from said engagement by sequentially grasping individual ones of the folded edges  
3 and individually lifting the items corresponding to the folded edges grasped away from  
4 said inclined surface.

1 31. (Withdrawn) Guiding, as set forth in clam 29, comprised of providing said  
2 inclined surface with an inclination of more than thirty degrees from horizontal.